

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page 6591)

Set post cor. secs. 21, 22, 27 and 28, from which
A Fir 60" dia., bears N.78°W., 45 lks. dist.
A Fir 24" dia., bears S.82°E., 36 lks. dist.
A Fir 12" dia., bears S.48°W., 44 lks. dist.
A Cedar 12" dia., bears N.22°E., 48 lks. dist.

Art. Boyer, Surveyor - Wit: R.H. Gee; Hendrikson - April 1949
- C.S. File 40/192

Found 3 orig. BTs and reset corner which is a 6" x 6" x 4 ft. Cedar post marked S21 S22 S27 S28 on respective sides.
60" Fir bears N.78°W., 29.7 ft. mkd. S21 T29S R8W BT 1581
26" Fir snag, bears S.48°W., 29.0 ft. mkd. ¼ S in bark.
28" Fir bears S.82°E., 23.8 ft. mkd. ¼ S in bark.
All being original trees.
New BT - 24" Fir bears S.37°W., 29.5 ft. mkd. S28 T29S R8W BT 1581.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1958 - C.S. File 49/100-32

Found - BTs as recorded by Boyer, 1949, except the NW. BT which is now down.
Scribed stake at corner.
The SW. BT, now stump.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 8 W
S 21 | S 22
S 28 | S 27
1958

New BTs- 12" Cedar bears N.39°E., 42.4 ft. scribed S22 T29S R8W CS BT.
10" W.Fir bears N.14°W., 15.3 ft. scribed S31 T29S R8W CS BT.
12" W.Fir bears S.45°W., 8.3 ft. scribed S28 T29S R8W CS BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2196, Surveyed Feb/March 2008 - (DCSO records Vol. 56 Page(s) 22284-5)

The cor. of secs. 21, 22, 27, & 28, perpetuated by Boyer, subsequently perpetuated by Byron, in 1958, monumented with an iron post, 1¼" dia., firmly set, projecting 13" above the ground, with brass cap (properly) mkd. cont. next pg

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree
A roothole bears S.71°E., 23.8 ft., with a sawed and uprooted fir stump, 31" dia., lying alongside, with no marks visible. (Record, S.82°E.)
and the remains of BTs by Byron, Deputy County Surveyor
A roothole bears N.37¼°E., 42.4 ft., with a fallen decayed cedar, 12" dia. lying alongside, with no marks visible.
A fir, 22" dia., bears S.28¾°W., 7.7 ft., with a healed blaze.
A fir, 22" dia., bears N.17¾°W., 16.1 ft., with a healed blaze.
and new bearing trees
A fir, 12" dia., bears N.49¼°E., 12.3 ft., mkd. T29S R8W S22 BT.
A fir, 18" dia., bears S.37¼°E., 17.4 ft., mkd. T29S R8W S27 BT.

Brent Knapp, i.e. engineering - Crew: N. Fromdahl, J. Ogden, and W. Keady - 11/2022 - C.S. File 65/111-26

Condition report only
Found - DCS0 brass cap (properly mkd)
24" Fir, bears S.28¾°W., 7.7 ft. healed blaze & tag.
24" Fir, bears N.17¾°W., 16.1 ft. healed blaze & tag
15" Fir, bears N.49¼°E., 12.3 ft. healed blaze & tag
20" Fir, bears S.37¼°E., 17.4 ft. healed blaze & tag
Note - Compass decl. 15°E.