

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6593)

Marked a Fir 6" dia., for ¼ sec. post, from which
A Fir 8" dia., bears S.75°E., 13 lks. dist.
A Fir 20" dia., bears S.20°W., 40 lks. dist.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 16996)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S R 8 W
1/4
S 16 | S 15
1982

from which

A Fir 15" dia., bears S.85°E., 20 lks. mkd. ¼ S15 BT.
A Fir 14" dia., bears N.24½°W., 30 lks. mkd. ¼ S16 BT.

Fd. Ok by G.Lang, 10/96 - 1997-0130

FD. Ok by Ken Hoffine - Sept. 2006 - M151-47

Fd. BC & BT; Set a 5½' fence post 1.5' North - 1/2013, by Troy Rambo - C.S. file 65/79-1

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - 9/2014 - M166-24A-D & M166-40 A-D

Found - 3¼" brass cap stamped BLM 1982 BT references
18.5" fir with healed face & tag dated 7/82,
S.85°E., 13.2'
19" Fir with healed face & tag dated 7/82 7/82,
N.24½°W., 19.8'.