TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6593)

Set ¼ sec. post, from which
An Oak 10" dia., bears S.22°W., 81 lks. dist.
An Oak 9" dia., bears N.18°E., 232 lks. dist.

A.N. Gould - Sept. 11, 1939 - C.S. File 62/35

Post gone but both BTs still standing with marks plain. Set Yewwood post marked with red chalk.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1970 - C.S. File 54/38-27

Looked for, not found.
Found E-W Blazes, good call on ridge 3 chains. Found some old B.Oak which had been opened. No trace of any evidence.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 16998)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd: T 29 S R 8 W

¼ S 10 / S 15
1980

from which
A Fir 15" dia., bears S.½°W., 10½ lks. dist. mkd. ¼ S15 BT
A Fir 16" dia., bears N.50°W., 37 lks. dist. mkd. ¼ S10 BT

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - 9/2014 - M166-24A-D & M166-40 A-D

Found - 3¼" brass cap stamped BLM 1980 BT references
15" Fir snag 12' tall with healed face and tag dated 7/80; S.0½°W., 6.9'
22" Fir with healed face tag dated 7/80; N.50°W., 24.4'
New BT - 21½" Chinquapin with blazed face and set tag dated 4/12/14; S.40°E., — 13.2' to nail side center

---