

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6594)

-----  
Set ¼ sec. post, from which  
A B.Oak 9" dia., bears N.66°E., 12 lks. dist.  
A Fir 12" dia., bears S.64°E., 20 lks. dist.

Arthur Boyer - For: F. Hurd - May 13, 1967 - C.S. File 55/35

-----  
Set ¼ corner by proportionate measurement.  
Drove 1/2" x 18" Iron pipe, brass elbow (½" pipe is inside 1" pipe), from which BTs:  
12" Fir bears S.66°W., 2.3 ft. scribed ¼ S10 1581 BT.  
8" pencil Cedar bears N.23½°E., 45.4 ft. on +18° slope, scribed ¼ S3 1581 BT.

Survey by Bruce Shaner - For: BLM - Aug. 25, 1972 - M 42-67

-----  
Set brass cap mkd. "T29S R8W WM 1/4S S3 S10 1972".  
Found - 3/4" Iron pipe set by Boyer, bears S.51 3/4°W., 13.42 ft.  
10" pencil Cedar BT, scribes visible, bears N.10°E., 32.1 ft. scribed by Boyer.  
30" orig. D.Fir BT stump, scribes "S10" visible, bears S.64°E., 13.2 ft.  
16" D.Fir BT, scribes partially visible, bears S.52°W., 15.6 ft. scribed by Boyer.

Fd. BC and BTs, Sept. 1986 by OSHD - C.S. File 63/9-38

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 17015-16)

-----  
The ¼ sec. cor., perpetuated and recorded by Shaner in 1972, monumented with an iron post 2½" dia., firmly set, projecting 8" above ground, with brass cap mkd. in 1972, from which the remains of the original bearing trees:  
A root hole bears N.66°E., 12 lks. dist., no tree remains.  
A sawed Fir stump 36" dia., bears S.64°E., 20 lks. dist., with scribe marks ¼ S10 visible on open decayed blaze.  
and new bearing trees:  
A Cedar 7" dia., bears N.61½°E., 46 lks. dist. mkd. ¼ S3 BT.  
A Fir 8" dia., bears S.39½°W., 47 lks. dist. mkd. ¼ S10 BT

(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

From this point, a cor. established by Boyer in 1967, by proportionate measurement, bears S.51 3/4°W., 0.219 chs. dist., monumented with an iron pipe 1/2" dia., inside of an iron pipe 1" dia., firmly set, projecting 18" above ground, from which bearing trees mkd.by Boyer:

A Cedar 8" dia., bears N.23°E., 66 lks. dist. with scribe marks ¼ S3 1581 BT visible on open blaze.

A Fir 18" dia., bears S.56°W., 3 lks. dist. with healed double blaze.