

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Pg 5794)

Set 1/4 sec. post, from which
A Fir 24" dia., bears North, 33 lks. dist.
A Fir 20" dia., bears S.22°E., 26 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Jan. 1969 - C.S. File 54/80 and M 37-25

Set Brass cap for 1/4 corner at proportional point midway between section corners, mkd: County Surveyors Office
T28S R8W 1/4 S 34
T29S S 3
1969

New BTs- 14" D.Fir N.72°E., 89.2 ft. mkd. 1/4 S34 CS BT.
12" D.Fir S.64°E., 65.1 ft. mkd. 1/4 S3 CS BT.
No trace of original BTs. This corner lies between old cat logging roads on moderate SE. slope approx. 400 ft. West of Nuns Creek.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause - Sept. 17, 1997 - C.S. 64/78-3

Found - 2 1/2" Brass cap on a 1 1/2" OD iron pipe protrudes 11" above ground (1969).
14" now 23" dia. D.Fir, with a fully healed double blaze, bears N.66 3/4°E., 89.2' agrees with BT tag by Shaner 6/72 (rec. per 1969 DCSO N.72°E., 89.2')
12" now 23" dia. D.Fir, with a fully healed double blaze, bears S.64°E., 64.1' (rec S.64°E. 65.1')
10" B.Oak no blazes visible with a 1972 Shaner line tag, bears S.73°E., 5.2' agrees with tag we double blaze and scribe "1/4 S3 CS BT".
New - 13" dia. D.Fir, double blazed and scribed "1/4 S34 CS BT", bears N.26°W., 20.8'.

Ron Quimby - J Leonard & J Laub - 4/2012 - C.S. File 65/76-41

Found - DCSO brass cap
28" D.Fir S.64°E., 64.1 ft. healed face.
10" Oak S.73°E., 5.2 ft.
14" Fir N.26°W., 20.8 ft. vis. scribes 1/4 S34 CS BT.
Down 24" Fir N.72°E., 89.2 ft. (Shaner Tag)
New - 10" D.Fir S.89°W., 67.1 ft. scribed S 1/4 BT.