

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6577)

- 
- Set post cor. secs. 34, 35, 2 and 3, from which
- A Cedar 15" dia., bears N.30°W., 13 lks. dist.
  - A Fir 40" dia., bears N.80°E., 21 lks. dist.
  - A Fir 20" dia., bears S.43°E., 46 lks. dist.
  - A Fir 30" dia., bears S.55°W., 6 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6610)

-----

Old established cor. to secs. 2, 3, 34 and 35, which is a post 4" sq., firmly set in the ground and mkd. T29S S35 on NE.; R8W S2 on SE.; S3 on SW.; and S34 on NW. faces. Also two notches on the E. and 4 notches on W. angles of same and from which

(Describes found BTs as described above)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Feb. 9, 1970 - C.S. File 54/38-24

- 
- Found - 40" D.Fir, now down, rotten, N.80°E., 13.9 ft.  
20" D.Fir now 27", S.43°E., 30.4 ft. Bark scribe visible "8 W 2".  
30" D.Fir, now down, rotten, S.55°W., 4 ft.  
15" Cedar, now down, N.30°W., 8.6 ft.

Set Brass cap at cor. mkd: County Surveyors Office  
T29S R8W S 34 | S 35  
T30S S 2  
1970

- New BTs- 26" D.Fir N.25°W., 20.2 ft. scribed T29S R8W S34 CS BT.  
8" W.Fir N.39°E., 21 ft. scribed T29S R8W S35 CS BT  
Reblazed and rescribed:  
27" D.Fir S.43°E., 30.4 ft. scribed T30S R8W S2 CSBT  
Corner lies approx. 230 ft. East of cor. for 2 & 3, T30-8

Fd. and used in BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15751-52)

continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54 Page(s) 20948-9)

-----  
The cor. of secs. 34 & 35 only on the S. bdy. of the Tp., monumented with an iron post, 1½" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree

A sawed fir stump, 33" dia., 10 ft. high, bears S.43°E., 30.4 ft., with a healed blaze.

and remains of bearing trees mkd. by the Douglas County Surveyor's Office

A roothole, bears N.39¾°E., 20.8 ft., with decayed trunk, size indeterminate, lying alongside, no marks visible.

A sawed fir stump, 30" dia., 6 ft. high, bears N.29½°W., 20.2 ft., with illegible scribe marks visible on a burnt partially healed blaze. (Record, 19.5 ft.)

and new bearing trees

A cedar, 8" dia., bears N.31¼°E., 37.7 ft., mkd. T29S R8W S35 BT.

A fir, 5" dia., bears S.70¼°W., 33.4 ft., mkd. T30S R8W S2 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

See last page for BLM Control Data Sheet.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

2/26/2004 **Control Data Sheet**  
 Bureau of Land Management  
 Oregon State Office  
 Branch of Geographic Sciences  
 Cadastral Survey Section

Control Station	NAD 83 (1991) Data
Station Name: 50010029S08W	Adjustment Software: TRIMNET PLUS
EC Number:	Geoid Computations: GEOID 96 v.1.00
County: DOUGLAS	Latitude: 42° 59' 49.66616"
State: OR	Longitude: 123° 37' 20.9347"
BLM District: ROSEBURG	Ellipsoid Height: 541.314 m
BLM Resource Area: SOUTH RIVER	Geoid Separation: -23.976 m
Location: T29S, R08W, SEC.35	MSL Elev (NAVD 88): 565.29 m
Meridian: WILLAMETTE	NAVD88 - NGVD29: 1.063 m
Mapping References	Error Ellipse (95%)
USGS 7½' QUAD: CAMAS VALLEY	Semi-Major: 0.02 m
USGS 15' QUAD:	Semi-Minor: 0.017 m
Group Number: 1972	Axis Azimuth: 169
Date Occupied: 3/26/2001	Vertical: 0.015 m
Method: GPS, STATIC, CARRIER PHASE	NAD 27 Data
Receiver Type: TRIMBLE 4600	Derivation: CORPSCON v.5.11
Baseline Software: GPSURVEY v.2.35	Latitude: 42° 59' 50.25065"
Vert Shift Software: VERTCON v.1.00	Longitude: 123° 37' 16.65616"

**Horizontal Reference Stations Utilized**  
 NGS Station WCAM (Order A), and Bureau of Land Mgt. Control Station 24040029S08W

**Description**  
 An iron post, 1 ¼ ins. diam., firmly set, projecting 12 ins. above the ground, with Douglas County Surveyors Office brass cap mkd.

T 29 S R 8 W  
 S 34 | S3 5  
 S 2  
 T 30 S  
 1979

HOW TO REACH: See quad sheet listed above for directions on how to reach this corner.

- Notes**
- Please send updated recovery information to: Branch of Geographic Sciences, Cadastral Survey Section (OR-957.1), Bureau of Land Management, P.O. Box 2965, Portland, Oregon, 97208. (503) 808-6132
  - All distances in "HOW TO REACH" description are in miles, unless otherwise noted