

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6585)

Set ¼ sec. post, from which
A Laurel 12" dia., bears N.70°W., 9 lks. dist.
A Fir 12" dia., bears N.20°E., 10 lks. dist.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15761)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 34 S 35
T 29 S R 8 W
1975

from which
A Fir 33" dia., bears N.50°E., 17 lks. dist. mkd. ¼ S35 BT.
A Fir 30" dia., bears N.30°W., 31 lks. dist. mkd. ¼ S34 BT