TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6586)

Set ¼ sec. post, from which
A Fir 10" dia., bears N.38°E., 7 lks. dist.
A Fir 12" dia., bears N.10°W., 15 lks. dist.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15764)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 22|S 23
T 29 S R 8 W
1975
from which
A W.Fir 13" dia., bears S.39°E., 33½ lks. dist. mkd. ¼ S23 BT.
A W.Fir 13" dia., bears N.53½°W., 21½ lks. dist. mkd. ¼ S22 BT.

Ron Quimby - 1/2008 - C.S. File 65/63-2

Found - 1975 BLM Brass cap
13" W.Fir S.39°E., 22.1 ft.
New - 17" Fir, N.25°E., 3.5 ft.
9" cedar N.81°W., 16.5 ft.
16" Fir, S.6°W., 21.0 ft.
All trees scribed ¼ S BT