TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6587-88)

Set ¼ sec. post, from which
An Oak 12" dia., bears N.87°E., 123 lks. dist.
An Oak 20" dia., bears N.68°W., 94 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1958 - C.S. File 49/100-25

Found - Orig. 20" now 24" Oak N.68°W., 62.0 ft. This BT down and has been down for years. I find good scribing "¼S" on previously opened face.
Find remains of old Oak that checks bearing and distance for original NE. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 8 W
¼ S15|S14
1958

New BTs- 15" R.Fir bears N.74°E., 11.2 ft. scribed ¼ S14 CS BT.
20" R.Fir bears N.61°W., 12.0 ft. scribed ¼ S15 CS BT.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15766)

The ¼ sec. cor., perpetuated and recorded by the county in 1958, monumented with an iron post 1¼" dia., firmly set, projecting 14" above ground with brass cap mkd. in 1958, from which the remains of the original bearing trees:
A root hole bears N.87°E., 123 lks. dist., with a down Oak alongside, size indeterminate, with fragmentary axe marks visible.
A root hole bears N.68°W., 94 lks. dist., with a down Oak alongside, 18" dia., with fragmentary scribe marks visible on decayed blaze.
and bearing trees mkd. by the county:
A Fir 17" dia., bears N.73 3/4°E., 16½ lks. dist., with healed blaze.
A Fir 25" dia., bears N.58¼°W., 18½ lks. dist., with healed blaze.
and a bearing tree of no record:
(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 25" dia., bears S.74 3/4°W., 41 lks. dist., with healed blaze.

Fd. and Used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 16991)

Ron Quimby - 2/2008 - C.S. File 65/63-10

Found - DCSO Brass cap (properly mkd)
17" Fir N.74°E., 10.9 ft. (Rotten snag)
30" Fir N.63°W., 10.9 ft. Good scar
33" Fir S.74°W., 27.1 ft. Good scar
New - 7" Fir S.37°E., 5.9 ft.
11" Fir N.36°E., 18.7 ft.
Both trees scribed ¼ S BT