

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6588)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.10°E., 24 lks. dist.
A Fir 40" dia., bears N.38°W., 51 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1958 - C.S. File 49/100-23

Found - Orig. 40" now 52" Fir snag N.38°W., 33.7 ft. I open near base and find good scribing "BT"
No trace of original NE. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 8 W
¼ S 10 | S 11
1958

New BTs- 16" R.Fir bears N.22½°E., 113.1 ft. scribed ¼ S11 CS BT.
14" R.Fir bears S.76°W., 61.3 ft. scribed ¼ S10 CS BT.

Fd. OK, July 14, 1986 by OSHD - C.S. File 63/9-21

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 16994)

The ¼ sec. cor., perpetuated and recorded by Byron in 1958, monumented with an iron post 1¼" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1958, from which the remains of an original bearing tree
A Fir snag 52" dia., bears N.38°W., 51 lks. dist. with scribe mark B visible on opened blaze.
and a bearing tree mkd. by Byron:
A Fir 18" dia., bears S.76°W., 93 lks. dist., with healed double blaze.
and a new bearing tree:
A Fir 8" dia., bears N.25½°E., 7 lks. dist. mkd. ¼ S11 BT.

Fd. OK by D. Edwards, Sept. 2000 - CS 65/29-6