TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6585)

Set ¼ sec. post, from which
A Laurel 12" dia., bears N.62°W., 20 lks. dist.
A Laurel 9" dia., bears S.70°E., 5 lks. dist.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15762)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 26
S 35
T 29 S R 8 W
1975

from which
A Fir 13" dia., bears N.10½°W., 41½ lks. dist. mkd. ¼ S26 BT.
A Fir 15" dia., bears S.42¼°E., 19 lks. dist. mkd. ¼ S35 BT.

Found OK by Hoffine, May 1997 - M 127-38
Found OK by D. Edwards, April 2003 - M142-6

David Edwards - Crew: Brant Miller & Eric Sprinkle - 7/2020 - C.S. 65/106-40

Found - BLM brass capped iron pipe. 1975 BLM BTs fd:
A 14" dia., 7' tall Fir stump (very rotted) bears N.10½°W., 27.4 ft.
An 18" dia. Fir bears S.42¼°E., 12.5 ft.
Both have healed blazes.
New - An 11" dia. Fir scribed "¼ S26 BT" bears N.9°E., 24.9 ft.
A six ft steel post is set 2 ft West.
Note - Compass decl. 15°E.