TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6586)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.70°E., 81 lks. dist.
A Fir 40" dia., bears S.66°E., 76 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 10, 1958 - C.S. File 49/100-40

Found - Orig. 40" now 58" down Fir. Open old scar and find good scribing "B"
No trace of orig. NE. BT.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 8 W
¼ S 23 / S 26
1958
New BTs- 30" R.Fir bears S.31°W., 17.0 ft. scribed ¼ S26 CS BT.
12" Cedar bears N.29°E., 39.7 ft. scribed ¼ S23 CS BT.
Corner under 4 ft. down Fir.

David Edwards - For: Roseburg Resources - 4/2003 (added 8/28/2024) - M142-6

Found - DCSO brass cap.
14" Cedar N.29°E., 39.7'
32" Fir snag S.31°W., 17.0'
New - 6" Fir N.42°E.. 21.85' "¼ S23 BT.