

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6588)

Set ¼ sec. post, from which
A B.Oak 12" dia., bears N.18°E., 96 lks. dist.
A Laurel 15" dia., bears S.30°E., 55 lks. dist.

Douglas Co. Surveyors Office - John M. Powell, and crew -
Aug. 1970 - C.S. File 54/38-27

Looked for, not found.
Found good E-W blazed line, old fence line, old logging to the South. No trace of any probable BTs. (Oak and Laurel)

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 16993)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 29 S R 8 W
1/4 $\frac{S\ 11}{S\ 14}$
1980

from which
A Grand Fir 8" dia., bears S.25½°E., 40½ lks. dist. mkd. ¼ S14 BT.
A Grand Fir 8" dia., bears N.64½°W., 31 lks. dist. mkd. ¼ S11 BT.

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - 9/2014 - M166-24A-D & M166-40 A-D

Found - 3¼" brass cap stamped BLM dated 1980
Note - No BTs found, BTs have fallen over or logged.
New BT - 51" Fir with blazed face and set tag dated 5/14/14;
N.11°W., 30.35' to nail side center
No trees available in section 14.