

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6589)

Set ¼ sec. post, from which
An Oak 20" dia., bears N.32°W., 73 lks. dist.
An Oak 12" dia., bears S.60°W., 64 lks. dist.

A. Boyer - Wit: R. Heater - Oct. 22, 1935 - C.S. File 16/70

Set a 3" x 3" Fir post and the following new trees set from original BTs:
A 30" B.Oak N.3°E., 111.0 ft.
A 14" W.Oak S.19½°W., 129.0 ft. (133 ft. on 14° slope measurement)
Original BT dead.

James W. Byron - For: C.W. Couey - May 5, 1954 - C.S. File 46/21 and M 6-68

Found 1½" x 1½" angle iron at corner. Both BTs as scribed by Boyer in 1935 in poor condition. Parts of scribing visible.
30" B.Oak N.3°E., measures 116.0 ft.
14" W.Oak S.19½°W., measures 128.0 ft.
We moved angle iron 4.7 ft. N.3°E. to fit Boyer's BTs for bearings and distances.
Blazed and scribed:
8" R.Fir N.39°E., 11.2 ft. "¼ S2 CS BT"
9" R.Fir S.29°W., 12.0 ft. "¼ S11 CS BT"

Survey by Herbert L. Northcraft - For: W.M. Sturmer - Sept. 1970 - M 40-79

Found - 1¼" angle iron for corner.
14" B.Oak, opened "¼" visible, reverse "B" on lower blaze, rescribed "¼ S11 T29S R8W"
New BT - 12" B.Oak N.28½°E., 31.2 ft. scribed "¼ S2 T29S R8W BT".

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 17019-20)

The ¼ sec. cor., perpetuated and recorded by Boyer in 1935, further perpetuated and recorded by Byron in 1954, further perpetuated and recorded by Northcraft in 1970, monumented with an angle iron, 1½" wide, firmly set, projecting 6" above
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

ground, from which remains of the original bearing trees:
 A root hole bears S.60°W., 64 lks. dist., no tree remains.
 A root hole bears N.32°W., 73 lks. dist., no tree remains.
 and bearing trees mkd. by Boyer:
 A burned Oak snag 20" dia., bears N.3°E., 170 lks. dist.,
 no marks visible.
 An Oak 14" dia., bears S.18½°W., 195 lks. dist., with
 scribe mark B visible on decayed blaze, rescribed by
 Northcraft, with scribe marks ¼ Cor S11 BT visible on
 open blaze.
 and bearing trees mkd. by Byron:
 A burned Fir stump size indeterminable bears N.39°E., 17
 lks. dist., no marks visible.
 A burned Fir root crown bears S.29°W., 18 lks. dist., no
 marks visible.
 and a bearing tree mkd. by Northcraft:
 A W.Oak 16" dia., bears N.28½°E., 48½ lks., with scribe
 marks 14 2 S visible on partially healed double blaze.
 At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
 directly atop the angle iron, with brass cap mkd:
 T 29 S R 8 W
 1/4 $\frac{S}{S 11}$
 1980

Fd. OK, July 15, 1986 by OSHD - C.S. File 63/9-22

Survey by Ronald Geisler - For: Champion International -
 March 1990 - C.S. File 63/113 and M 109-72

 Found - 1980 BLM 3½" BC/IP, 5" above ground.
 20" burned Oak snag 15 ft. tall, bears N.3°E., 112.7
 ft. (Rec. 111.0 ft.) Rotted face. (1935)
 14" W.Oak bears S.18½°W., (Rec. S.19½°W.) 129.0 ft.
 partial scribing visible. (1935)
 Burned Fir stump bears N.39°E., 11.2 ft. (1954)
 Burned Fir stump bears S.29°W., 12.0 ft. (1954)
 18" B.Oak bears N.28½°E., 31.7 ft. (Rec. 31.2 ft.)
 Closed face.
 New BTs- 9" Fir bears S.23°W., 48.89 ft. scribed ¼ S11 BT.
 23" Fir bears S.88°W., 143.89 ft. scribed ¼ S11 BT.
 No BTs available in the SE. quadrant.

Fd. Ok by D.Edwards, 2/1999 - M131-29
 Fd. Ok by Gary Smithers - April 2002 - M140-3
 Fd. OK by D. Edwards, July 2003 - M142-64
 Fd. OK by D. Edwards, Oct. 2007 - M154-30