

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 2; & 35, T28-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5793)

Set ¼ sec. post, from which
A B.Oak 12" dia., bears N.58°W., 238 lks. dist.
A W.Oak 18" dia., bears S.83°E., 94 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Jan. 1969 - C.S. File 54/80 & M 37-25

Set brass cap for ¼ cor. at the proportional point midway
between section corners, cap mkd: County Surveyors Office
T28S R8W ¼ $\frac{S\ 35}{S\ 2}$
T29S
1969

New BTs- 12" D.Fir N.55°W., 42.5 ft. mkd. ¼ S35 CS BT.
13" D.Fir S.60°W., 47.9 ft. mkd. ¼ S2 CS BT.
Corner lies 10 ft. East of creek, 2 ft. wide, course SE.,
curving to South. We find no trace of original BTs.

Fd. and accepted in BLM resurvey by Wayne L. Rogers,
Cadastral Surveyor, Group #1483, surveyed May/July 1989 -
(DCSO records Vol. 50 Page(s) 18842)

Fd. Ok by Gary Smithers - April 2002 - M140-3