

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 574100

PRIMARY CORNER DESCRIPTION C.C. for Secs. 1 & 2 only, T30-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6609)

-----  
Set a Maple post 4" triangular, 4 ft. long, 20" in the ground mkd. T29S R8W S35 on the N.; T30S S1 on SE.; S2 on the SW.; for the cor. to secs. 1 and 2, from which

A Fir 15" dia., bears N.2°E., 30 lks. dist. mkd. T29S R8W S35 BT.

A Fir 24" dia., bears S.24°E., 75 lks. dist. mkd. T30S R8W S1 BT.

A Cedar 10" dia., bears S.59°W., 61 lks. dist. mkd. T30S R8W S2 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1967 - C.S. File 54/38-17

-----  
Found - 10" Cedar now 13", S.67°W., 43.8 ft. (Rec. S.59°W., 40.3 ft.) Opened for scribe "T".

15" now 30" D.Fir N.2°E., 19.8 ft., faint ark scribe "T R".

24" D.Fir now 30" stump, S.33°E., 49.5 ft. (Rec. S.24°E.) Faint bark scribe "B S".

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 8 W

S 35

S 2 | S 1

T 30 S R 9 W

1967

New BT - 30" D.Fir N.84°E., 27.6 ft. mkd. T29S R8W S35 CS BT  
No good trees in section 1.

Corner lies 5.0 ft. East of ravine.

Fd. and used in BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15750-51)

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Jan. 9, 1980 - M 79-15

-----  
Found - 1970 DCSO brass cap/iron pipe (Rec. 1967)  
30" Cedar S.59°W., 40.3 ft., orig. record. (1967 rec., S.67°W., 43.8 ft.)

New BT - 12" Maple bears S.50°E., 57.4 ft. (5.81 ft. North of Tp. line.)