TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6579)

Set ¼ sec. post, from which
A Fir 10" dia., bears N.58°E., 61 lks. dist.
A Fir 15" dia., bears N.15°W., 20 lks. dist.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15754)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 35 S 36
T 29 S R 8 W
1975

from which
A Fir 8" dia., bears S.73°E.,23½ lks. dist. mkd. ¼ S36 BT
A Fir 14" dia., bears S.65¼°W., 25½ lks. dist. mkd. ¼ S35 BT.