

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6579)

- 
- Set post cor. secs. 25, 26, 35 and 36, from which
- A Hemlock 15" dia., bears N.22°W., 57 lks. dist.
  - A Hemlock 5" dia., bears S.64°W., 35 lks. dist.
  - A Fir 50" dia., bears N.28°E., 58 lks. dist.
  - A Fir 10" dia., bears S.47°E., 62 lks. dist.

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 6024)

-----

The point for cor. of secs. 25, 26, 35 and 36, located by measurement from the NE. and NW. bearing trees. The SE. and SW. bearing trees have rotted away.

At the exact corner point  
Set an iron post, 28" long, 2" dia., 28" in the ground, with brass cap mkd:

T 29 S R 8 W  
S26:S25  
S35:S36  
1924

- from which the original bearing trees:
- A Fir 60" dia., bears N.28°E., 58 lks. dist. marks are plain on the bark.
  - A Hemlock 24" dia., bears N.22°W., 57 lks. dist., marks grown over.

- New Bearing trees:
- A Hemlock 10" dia., bears N.82°E., 90 lks. dist. mkd. T29S R8W S25 BT.
  - A Fir 26" dia., bears S.53°E., 62 lks. dist. mkd. T29S R8W S36 BT.
  - A Hemlock 14" dia., bears S.66½°W., 112 lks. dist. mkd. T29S R8W S35 BT.
  - A Hemlock 8" dia., bears N.46°W., 56 lks. dist. mkd. T29S R8W S26 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - April 1967 - C.S. File 54/38-19

-----

Found - GLO brass cap, properly mkd. in 1924.  
Orig. 24" now 30" Hemlock, N.22°W., 37.6 ft., very faint scar visible.  
Orig. 60" Fir, now stump, N.28°E., 38.3 ft., burnt cat face.

(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" now 11" (12 ft. snag) N.82°E., 59.4 ft., scribe visible.  
26" now 29" Hemlock, (Rec. D.Fir) S.53°E., 40.9 ft.  
14" now 20" Hemlock N.46°W., 37.0 ft., scribe visible, tree is rotting.  
8" now 18" Hemlock N.66½°W., 73.9 ft., shows good scar.  
New BTs- 10" Hemlock N.74°E., 31.0 ft. mkd. T29S R8W S25 CSBT.  
7" Hemlock S.33°W., 15.6 ft. mkd. T29S R8W S35 CSBT  
Corner lies about 300.0 ft. S. of old road at the end.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15755)

-----  
The Sec. cor., monumented with an iron post ½" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1924, from which the remains of the original bearing trees:  
A sawed Fir stump 60" dia., bears N.28°E., 58 lks. dist., with healed blaze.  
A Hemlock 33" dia., bears N.22°W., 57 lks. dist., with fragmentary scribe marks visible on open blaze.  
and the remains of bearing trees mkd. by Mensch:  
A Hemlock snag 12" dia., bears N.82°E., 87 lks. dist., with fragmentary scribe marks visible on open blaze. (Rec. 90 lks.)  
A Hemlock 29" dia., bears S.53°E., 62 lks. dist., with scribe marks T29S R8W S36 BT visible on open blaze. (Rec. Fir)  
A Hemlock 22" dia., bears S.66½°W., 110 lks. dist., with fragmentary scribe marks visible on open blaze. (Rec. 112 lks.)  
A root hole bears N.46°W., 56 lks. dist., with a down Hemlock alongside 18" dia., with healed blaze.  
and bearing trees mkd. by the County in 1967:  
A Hemlock 13" dia., bears N.72½°E., 46½ lks. dist. with scribe marks T29S R8W S25 CS BT visible on open blaze.  
A Hemlock 10" dia., bears S.34°W., 22½ lks. dist. with scribe marks T29S R8W S35 CS BT visible on open blaze.  
and a new bearing tree:  
A Hemlock 9" dia., bears N.69°W., 75 lks. dist., mkd. T29S R8W S26 BT.  
Add marks 1975 to brass cap.

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine for Lone Rock Timber Co. May 1997 - M 127-38  
-----

Found - G.L.O. brass cap 0.3 feet above ground.

14" Hemlock bears N.78°W., 7.0 ft. (rec. N.73½°W., 6.8 ft. per old B.L.M. tag) (no previous record)

32" Hemlock snag, bears N.20°W., 38.3 ft. (rec. N.22°W., 37.6 ft.) County BT tag

13" down Hemlock with County tag, S.33°W., 15.6 ft.

28" down Fir with B.L.M. tag, S.53°E., 40.9 ft.

Note - Corner lies on steep south facing slope approximately 75 ft. north of flat bench by Main Creek.