

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6581)

-
- Set post cor. secs. 13, 14, 23 and 24, from which
- A Laurel 5" dia., bears S.20°E., 16 lks. dist.
 - A Laurel 5" dia., bears S.30°W., 8 lks. dist.
 - A Laurel 5" dia., bears N.75°W., 11 lks. dist.
 - A Laurel 6" dia., bears N.33°E., 21 lks. dist.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 6028-29)

Intersect the point for cor. of sec. 13, 14, 23 and 24, located by measurement from the original bearing trees.
At the exact cor. point
Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap marked:

T29S:R8W
<u>S14:S13</u>
S23:S24
1924

- from which the original bearing trees:
- A Laurel 14" dia., bears N.33°E., 21 lks. dist., marks grown over.
 - A Laurel 10" dia., bears S.20°E., 16 lkws. dist. marks grown over.
 - A Laurel 8" dia., bears N.75°W., 11 lks. dist., marks grown over.
- SW. BT, rotted down.
- New bearing trees:
- A Cedar 6" dia., bears N.40°E., 9 lks. dist. mkd. T29S R8W S13 BT.
 - A Fir 38" dia., bears S.37°E., 48 lks. dist. mkd. T29S R8W S24 BT.
 - A Laurel 10" dia., bears S.81°W., 46 lks. dist. mkd. T29S R8W S23 BT.
 - A Fir 8" dia., bears N.7°W., 16 lks. dist. mkd. T29S R8W S14 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov/Dec. 1966 - C.S. File 54/38-12

Found - GLO brass cap, properly mkd. in 1924.
6" now 8" Cedar N.40°E., 5.9 ft., scribe visible
"T29S R8W S13 BT"
38" now 40" Fir S.37°E., 31.7 ft., shows good scar.
(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

8" now 11" D.Fir N.7°W., 10.6 ft., shows good scar.
10" Laurel S.81°W., 30.4 ft. Tree had been badly cut
up and rotted.
New BTs- 10" Cedar S.36½°W., 33.0 ft. mkd. T29S R8W S23 CSBT

Fd. and used BLM resurvey by Charles E. Akin, Jr.; James E. Jolley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15757)

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy and crew - April 26, 1977 - C.S. File 59/31-32

CONDITION REPORT ONLY

Found a 2" I.P. extending 8" above ground, with brass cap attached as marked in 1924, from which

An Orig. 5" now 8" dead fork of a Madrone, rotted, with no marks visible, bears N.75°W., 7.3 ft.

An Orig. 6" now 11" Madrone, alive, no marks visible, bears N.33°E., 13.9 ft.

The orig. SE. and SW. bearing trees are gone.

1924 BT, A 6" now 7" I.Cedar, alive with scribing "8W S13 BT" visible on partially healed single blaze, bears N.40°E., 5.9 ft.

1924 BT, a 38" now 40" D.Fir, alive and well healed, bears S.37°E., 31.7 ft.

1924 BT, a 10" now 8" Madrone, alive, no marks visible on rotted blazes, bears S.81°W., 30.4 ft.

1924 BT, an 8" now 12" D.Fir, alive with well healed double blaze, bears N.7°W., 10.6 ft.

1966 BT, a 10" now 8" I.Cedar, alive with scribing "T29S R8W S23 CS BT" visible on a double blaze, bears S.36½°W., 31.7 ft. (Rec. S.36½°W., 33.0 ft.)

Ron Quimby - 1/2008 - C.S. File 65/63-1

Condition report only

Found - 1924 GLO Brass Cap

12 madrona, N.33°E., 13.9 ft.

9" cedar, N.40°E., 5.9 ft.

42" Fir, S.37°E., 31.7 ft.

11" cedar, S.36½°W., 31.7 ft.