

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6582)

Marked an Oak 12" dia. for cor. of secs. 11, 12, 13 and 14, from which

- A Laurel 15" dia., bears N.78°E., 42 lks. dist.
- A Laurel 12" dia., bears S.52°E., 29 lks. dist.
- An Oak 12" dia., bears S.78°W., 13 lks. dist.
- A Pine 36" dia., bears N.50°W., 31 lks. dist.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 6030-31)

Intersect the point for cor. of secs. 11, 12, 13 and 14, where I find a stump hole indicating the position of the original corner tree, further identified by measurement from the original bearing trees.

At the exact cor. point

Set an iron post 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T29S:R8W

S11:S12

S14:S13

1924

from which original bearing trees:

- A Laurel stump bears N.74°E., 42 lks. dist., not N.78°E.
- A Laurel stump bears S.52°E., 26 lks. dist., not 29 lks.
- A B.Oak 18" dia., bears S.78°W., 13 lks. dist., marks grown over, blazes are plain.
- A Pine stump 36" dia., bears N.54°W., 31 lks. dist., not N.50°W., marked BT.

New Bearing trees:

- A Fir 9" dia., bears N.64°E., 18 lks. dist. mkd. T29S R8W S12 BT.
- A Fir 12" dia., bears S.82°E., 20 lks. dist. mkd. T29S R8W S13 BT.
- A Fir 10" dia., bears S.66°W., 7 lks. dist. mkd. T29S R8W S14 BT.
- A Fir 7" dia., bears N.33°W., 14 lks. dist. mkd. T29S R8W S11 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1966 - C.S. File 54/38-3

Found - 1924 GLO brass cap, properly marked.
18" B.Oak S.78°W., 8.6 ft., now gone.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

9" Fir, now down, N.64°E., 11.9 ft., found scribing "BT"
12" Fir now 15", S.82°E., 13.2 ft., shows good scar
10" now 18" Fir, S.66°W., 4.6 ft., shows good scar.
7" now 10" Fir N.33°W., 9.2 ft., this tree leaning badly.
New BTs- 13" D.Fir N.40°E., 16.5 ft. mkd. T29S R8W S12 CS BT.
9" D.Fir N.72°W., 15.9 ft. mkd. T29S R8W S11 CS BT.

Douglas Co. Surveyors Office - L.E. Monrean; Rod Kimberling, crew - April 7, 1977 - C.S. File 59/31-22

Found - 1924 GLO brass cap 4" above ground, firmly in place, properly mkd.
Orig. 36" Pine, now uprooted and badly decayed bears N.54°W., 20.5 ft. to center of root hole. No scribing found.
No other original BTs found.
A Fir 12" now 15", bears S.82°E., 13.2 ft. Tree has well healed single blaze. (1924 BT)
A Fir 10" now 20", bears S.66°W., 4.6 ft. Tree has well healed blaze. (1924 BT)
A 7" Fir now a 10" snag, 10 ft. high, bears N.33°W., to center at top of blaze, 9.2 ft., center of base of snag bears N.28½°W. Snag has well healed blaze. (1924)
NE. BT is gone.
1966 BT, a 9" D.Fir now 15" stump, bears N.42½°E., 16.5 ft., bottom of blaze remaining on stump, partially healed scribed "2 CS BT".
1966 BT, a 9" Fir now uprooted, bears N.72°W., 15.9 ft. Tree blazed some scribe marks visible, we do not open blaze.
New BTs- Fir 15" bears N.44°W., 64.9 ft., double blazed and scribed T29S R8W S11 CS BT.
Madrone 40" bears N.25°E., 48.1 ft., double blazed and scribed T29S R8W S12 CS BT.
Corner lies at the corner of clear cuts to the NE. and SW.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 16987-88)

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - 9/2014 - M166-24 A-D & M166-41A-D

Found - 2½" brass cap stamped US GLO dated 1924
continued next page

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

43" Madrone with healed face and tag dated 4/7/77;
N.25°E., 48.1'
26" Fir with healed face and tag dated 4/58;
S.81°E., 12.0'
26 Fir with blazed face & tag dated 4/58; S.66°W. 3'
New BT - 5" Fir with blazed face and set tag dated 5/10/14;
N.13°W., 13.4' to nail side center
12" Fir with blazed face and set tag dated 5/10/14;
N.40°E., 47.1' to nail side center.