

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6583)

Set ¼ sec. post, from which
A Fir 30" dia., bears N.3°W., 30 lks. dist.
A Laurel 12" dia., bears S.89°E., 68 lks. dist.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 28, 1966 - C.S. File 54/38-4

Found - Orig. 12" now 17" Laurel S.89°E., 44.9 ft., opened for scribe "¼".
Orig. 30" now 40" D.Fir N.3°W., 19.8 ft. This tree badly cut up on face.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 8 W
¼ S11 | S12
1966

New BTs- 9" Laurel S.49°E., 16.1 ft. mkd. ¼ S12 CS BT.
7" Hemlock N.76°W., 9.5 ft. mkd. ¼ S11 CS BT.

Douglas County Surveyors Office - Gary L. Langlitz, Deputy - Frank C. Silagy; Terrie Plouff, crew - Oct. 2, 1978 - C.S. File 60/17-8

Found - 1" Iron pipe extending 16" above ground with properly mkd. 1966 brass cap.
No trace of orig. corner post.
Orig. 30" D.Fir now a 40" stump, no markings found, bears N.3°W., 19.8 ft.
Remains of an orig. BT, a 12" Laurel now a 17" dia. 6 ft. tall stump, previously opened, no markings visible, bears S.89°E., 46.3 ft. (Rec. S.89°E. 44.9 ft.)
9" Laurel now 10" and uprooted, root hole bearing approx. S.47°E., 14.6 ft. scribing "¼ S12 CS BT" visible on unhealed double blaze.
7" Hemlock now 9" dia., 6 ft. tall stump with well healed double blaze, bears N.71°W., 9.5 ft. (Rec. N.76°W., 9.5 ft.)

At the position of the found 1966 monument and the exact corner point, we reset said monument to extend 2" above ground.

New BTs- 7" D.Fir scribed "¼ S12 CS BT" on a double blaze, bears S.43°E., 34.3 ft.
8" Grand Fir scribed "¼ S11 CS BT" on a double blaze, bears S.4°W., 64.6 ft. (Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner located in logged area. Placed location poster approx. 175 ft. West of logging road. Placed survey marker post and sign approx. 1 ft. East of the corner.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1027, surveyed May 1980/Aug. 1982 - (DCSO records Vol. 44 Page(s) 16989)

Fd. OK by D. Edwards, Sept. 2000 - CS 65/29-6
Fd. OK by D. Edwards, July 2003 - M142-64