

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6583)

-----  
Set post, cor. secs. 1, 2, 11 and 12, from which  
A Laurel 12" dia., bears S.81°E., 41 lks. dist.  
A Fir 36" dia., bears N.26°E., 39 lks. dist.  
A Cedar 40" dia., bears N.15°W., 47 lks. dist.  
A Cedar 36" dia., bears S.75°W., 41 lks. dist.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 6034)

-----  
Intersect the point for cor. of secs. 1, 2, 11 and 12, located by measurement from the original bearing trees.

At the exact cor. point  
Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap marked:  
T29S:R8W  
S2:S1  
S11:S12  
1924

from which the original bearing trees  
A Fir 40" dia., bears N.26°E., 39 lks. dist. marks are plain.  
A Cedar 40" dia., bears S.75°W., 41 lks. dist. plainly marked.  
A Fir 12" dia., bears N.15°W., 48 lks. dist., plainly marked (not a Cedar 40" dia. N.15°W., 47 lks.)  
New bearing tree:  
A Fir 12" dia., bears S.51½°E., 77 lks. dist. mkd. T29S R8W S12 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 28, 1966 - C.S. file 54/38-5

-----  
Found - 1924 GLO brass cap, properly marked.  
40" D.Fir now stump, N.26°E., 25.7 ft.  
40" Cedar, now down, S.75°W., 27.1 ft., opened for scribe.  
12" now 18" Fir N.15°W., 31.7 ft., shows good scar.  
No trace of SE. BT.  
New BTs- 18" Cedar N.41°E., 55.0 ft. mkd. T29S R8W S1 CS BT.  
14" D.Fir S.67°W., 59.3 ft. mkd. T29S R8W S11 CS BT.  
19" W.Fir S.16°E., 37.1 ft. mkd. T29S R8W S12 CS BT.

Fd. OK, Aug. 1981 by R. Kimberling - M 88-16  
Fd. OK, July 1986 by OSHD - C.S. File 63/9-20 "M-8 & "M-3"

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Ronald Geisler - For: Champion International -  
March 16, 1990 - C.S. File 63/113 and M 109-72

-----  
Found - 1924 GLO 2½" brass cap on a 2" I.P., 12" above  
ground.

21" Fir bears N.13°W., 31.7 ft. (Rec. N.15°W., 31.0  
ft.) Closed face (Orig. BT)

Rotted stump bears N.26°E., 25.7 ft. to face. Orig.

Uprooted Cedar bears S.75°W., 27.1 ft. (Orig.)

27" Fir bears S.12°E., 37.1 ft. (Rec. S.16°E.)  
Closed face.

25" Cedar bears N.46°E., 53.5 ft. (Rec. N.41°E.,  
55.0 ft.) Closed face.

14" Fir bears N.88°W., 53.3 ft., opened face at base  
but found no scribing. (No record)

Did not find 1966 BT, S.67°W., 59.3 ft.

New BT - 5" W.Oak bears S.82°W., 14.13 ft. scribed T29S R8W  
S11 BT.

Fd. OK by D. Edwards, July 2003 - M142-64