

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 1 and 2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6584)

-----  
Set 1/4 sec. post, from which  
A Fir 10" dia., bears S.23°E., 37 lks. dist.  
A Fir 24" dia., bears S.79°W., 62 lks. dist.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 6035)

-----  
Proportionate distance.  
Set an iron post 3 ft. long, 1" dia., 28" in the ground for 1/4 sec. cor., with brass cap marked: 1/4  
S2:S1  
1924

from which  
A W.Oak 6" dia., bears N.27 1/2°E., 110 lks. dist. mkd. 1/4 S1 BT.  
A W.Oak 14" dia., bears N.17°W., 92 lks. dist. mkd. 1/4 S2 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb. 20, 1969 - M 37-25 and C.S. File 54/80

-----  
Set brass cap for 1/4 corner as we find no trace of 1924 brass cap or BTs.  
Set at prorated distance and mkd: County Surveyors Office  
T 29 S R 8 W  
1/4 S 2 S 1  
1969

New BTs- 28" W.Oak N.84°E., 113.9 ft. mkd. 1/4 S1 CS BT.  
29" W.Oak S.88°E., 112.2 ft. mkd. 1/4 S1 CS BT.  
There were no trees available to West of line.

Fd. Ok - G Baughman - March 1977 - M65-8 (info added 3/2002)  
Fd. Ok by Gary Smithers - April 2002 - M140-3