

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 620440

PRIMARY CORNER DESCRIPTION Center W. 1/16 cor. Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15779-80)

-----  
Point for the center W 1/16 sec.cor. of sec. 13.  
Set an iron post 28" long, 2½" dia., 20" in the ground, with brass cap marked:  
C  $\frac{W\ 1/16}{S\ 13}$  C  
1975

from which  
A Fir 6" dia., bears S.13°E., 18 lks. dist. mkd. CW 1/16 S13 BT.  
A Fir 20" dia., bears N.59°W., 40 lks. dist. mkd. CW 1/16 S13 BT.

Douglas County Surveyors Office - Gary L. Langlitz, Deputy and crew - May 9, 1977 - C.S. File 59/34-10

-----  
Found - A 2½" I.P., firmly set extending 8" above ground with standard BLM brass cap attached mkd. in 1975.  
An unrecorded 1" I.P. extending 12" above ground bears S.71°E., 2.4 ft. from the brass cap.  
A 6" now 8" Grand Fir with scribing "CS 1/16 S13 BT" visible on unhealed double blaze, bears S.16°E., 11.9 ft. (Rec. S.13°E., 11.9 ft.)  
A 20" now 20" Grand Fir with scribing "CW 1/16 S13 BT" visible on unhealed single blaze, bears N.61½°W., 26.4 ft. (Rec. N.59°W., 26.4 ft.)

Did Not Renew.  
(Note; At the time of Langlitz visit, the 1975 BLM survey had not been recorded with the county.) (Unofficial notes were recorded in C.S. File 58/82) V.Laugen, March 1997