

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6576)

-----  
Set ¼ sec. post, from which  
A Fir 30" dia., bears N.19°W., 17 lks. dist.  
A Yew 12" dia., bears S.87°E., 20 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6608)

-----  
Old ¼ sec. cor. post and witness tree standing.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1967 - C.S. File 54/38-18

-----  
Found - 30" now 38" D.Fir N.19°W., 11.2 ft., bark scribed "¼S", good "BT" scar.

No trace of SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 8 W  
¼ S 36  
T 30 S  
1967

New BTs- 6" W.Fir N.4°E., 31.2 ft. mkd. ¼ S36 CS BT.  
15" Cedar S.11°E., 20.2 ft. mkd. S1 CS BT.

No other good trees in North to scribe.

Douglas Co. Surveyors Office - John M. Powell, and crew - July 5, 1972 - C.S. File 54/38-33

-----  
Found - 1967 DCSO brass cap at corner, out of position due to logging.

6" now 7" W.Fir N.4°E., 31.2 ft., shows good scar.  
15" Cedar now high stump, S.11°E., 20.2 ft., scribe visible.

Reset brass cap at ¼ corner.

New BT - 11" Cedar N.89°E., 112.2 ft. scribed "¼ S36 CS BT"