

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6579)

-----  
Set ¼ sec. post, from which  
A Fir 30" dia., bears S.78°E., 40 lks. dist.  
A Laurel 4" dia., bears N.57°W., 20 lks. dist.

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 6023)

-----  
The point for ¼ sec. cor., located by measurement and record bearing from the original SE. bearing tree, on the burnt bark of which the blazes are plain.

At the exact corner point  
Set an iron post, 28" long, 1" dia., 28" in the ground, with brass cap mkd:  
¼     S 25  
       S 36  
       1924

from which original bearing trees:  
A Fir 40" dia., bears S.78°E., 40 lks. dist.  
New bearing trees:  
A Fir 28" dia., bears S.47°E., 86 lks dist. mkd. ¼ S36 BT.  
A Fir 10" dia., bears N.89°W., 81 lks. dist. mkd. ¼ S25 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 7, 1970 - C.S. File 54/38-28

-----  
All BTs OK and tagged. Brass cap firmly in ground.