

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6581)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears S.59°E., 12 lks. dist.  
A Fir 24" dia., bears N.28°W., 17 lks. dist.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 6028)

-----  
Intersect the point for the ¼ sec. cor., located by measurement from the original bearing trees.  
At the exact cor. point  
Set an iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor., with brass cap mkd. ¼  $\frac{S\ 13}{S\ 24}$   
1924

from which the original bearing trees:  
A Fir 36" dia., bears N.28°W., 17 lks. dist. marks plain on the bark.  
A Fir, now dead, 32" dia., bears S.59°E., 12 lks. dist., marks are on the bark.  
New bearing trees:  
A Fir 30" dia., bears S.53°W., 27 lks. dist. mkd. ¼ S24 BT  
A Fir 36" dia., bears N.73°W., 59 lks. dist. mkd. ¼ S13 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - July 22, 1970 - C.S. File 54/38-26

-----  
Found - 1924 GLO brass cap, in place & properly mkd.  
30" Fir, now badly decayed, S.53°W., 17.8 ft., find scribe and reverse.  
36" Fir, now stump, N.73°W., 38.9 ft. scribe visible.  
Both original BTs also in evidence but badly decayed with bark gone.  
New BTs- 11" D.Fir N.83°W., 20.1 ft. mkd. ¼ S13 CS BT.  
8" D.Fir S.60°W., 17.6 ft. mkd. ¼ S24 CS BT.  
5" D.Fir S.88°E., 12.6 ft. mkd. ¼ S24 CS BT.  
Corner lies on steep, westerly slope in dense second growth, old cutting line bears North approx. 200 ft.

Fd. and used in BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Con. #52500-CT5-1117 - Surveyed June 1973/April 1976. Group #'s808; 858; 860, - (DCSO rec. Vol. 39 Page(s) 15756)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - P. L. Earle, crew - Feb. 22, 1977 - C.S. File 59/29-30

-----  
Found - 1924 GLO brass cap in good condition, firmly set, properly marked.  
Orig. Fir 24", now a badly decayed stump, 30" approx. 10 ft. high. I open and find good scribing "BT". Trees bears S.59°E., 7.9 ft. to face (rec.) and 8.4 ft. to center.  
Orig. Fir 24", now a badly decayed stump 28", 8 ft. high. Tree has old blaze. We do not open. Tree bears N.28°W., 11.2 ft. to center.  
1924 BT, a 30" Fir, now a badly decayed stump, dia. of remaining heart wood 14", 10 ft. high. Tree has partially healed blaze, fragmentary scribing visible, bears S.53°W., 17.8 ft.  
1924 BT, a Fir, now a 33" stump, 4 ft. high. Scribing visible "S13 BT". Stump bears N.73°W., 37.3 ft. to center. (Rec. 38.9 ft.)  
1970 BT, a 11" D.Fir now 13" bears N.83°W., 19.8 ft. (Rec. 20.1 ft.) Tree has partially healed double blaze, some scribing visible "3 CS BT"  
1970 BT, a 8" now 9" D.Fir bears S.60°W., 17.6 ft. Tree has partially healed double blaze, scribed "B" visible.  
1970 BT, a 5" now 6" D.Fir bears S.88°E., 12.6 ft. to center. Tree has partially healed blaze, scribing partially covered.

We do not renew.

Survey by Mark Smalley -For: Kenneth Ford - Dec. 1994  
- M 121-51

-----  
Found - GLO brass cap and iron pipe.  
36" Fir N.73°W., 37.3 ft., stump.  
28" Fir N.28°W., 11.2 ft., rotten snag. Original  
7" Fir S.88°E., 12.6 ft., healed.  
24" Fir S.29°E., 8.4 ft., snag, scribe visible. Orig  
9" Fir S.60°W., 17.6 ft., down.  
Scribed- 10" Fir N.5°W., 25.8 ft. "¼ S BT"  
10" Fir N.22°E., 22.7 ft. "¼ S BT"  
5" Fir S.8°E., 28.2 ft. "¼ S BT"