

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 640540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy -
Wit: Virginia Laugen; Deloris Keady - Dec. 18, 1978 - C.S.
File 60/24-1 and 59/41

Found - A 1" alum. tube covering an iron rod, bears N.69°E.,
19.33 ft. dist. from proper corner. Rod and
tubing extend 18" above ground.

Set a 1½" x 36" I.P. with brass cap mkd. "Douglas County
Surveyor T29S C 1/4 + S12 R8W 1978", buried 35" in the
ground. Corner set by intersection N & S 1/4 and W & E 1/4
Corner.

Accessories:

A 10" D.Fir bears S.4½°W., 14.4 ft. mkd. "C ¼ S12 CS
BT" in a double blaze.

A 14" D.Fir bears S.53°W., 29.2 ft. mkd. "C ¼ S12 CS
BT" in a double blaze.

A 22" incense Cedar bears N.77°W., 43.8 ft. mkd. "C
¼ S12 CS BT" in a double blaze.

A 4 x 7 ft. conglomerate rock outcropping with 2 ft.
vertical face, bears N.15°E., 10.6 ft. mkd.
"BO+". "+" is 4" high.

A steel fence post bears North, 1 ft. with surveyor
marker sign attached.

Corner located on fairly steep hill side.

FD. Ok by Ken Hoffine, 8/2007 - M154-14