

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 660440

PRIMARY CORNER DESCRIPTION E 1/16 Sec. 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15779)

Point for the center E 1/16 sec. cor. of sec. 13.
Set an iron post 28" long, 2½" dia., 20" in the ground, with brass cap marked:
C $\frac{E\ 1/16}{S\ 13}$ C
1975

from which
A fir, 10" dia. bears N.81°E., 27 lks. mkd: CE 1/16 S13 BT
A fir, 8" dia. bears S.64°W., 28 lks. mkd: CE 1/16 S13 BT

Douglas County Surveyors Office - Gary L. Langlitz, Deputy and crew - May 16, 1977 - C.S. File 59/34-16

Found - A 2½" I.P., firmly set extending 8" above ground with standard BLM brass cap attached mkd. in 1975.
A 8" D.Fir now 10" bears S.64°W., 18.5 ft. mkd "CE 1/16 S13 BT" in open single blaze.
A 10" D.Fir now 11" bears N.83°E., (rec. N.81°E.) 17.2 ft. (rec. 27 lks.) mkd "CE 1/16 S13 BT" in open single blaze.

Did Not Renew.
(Note; At the time of Langlitz visit, the 1975 BLM survey had not been recorded with the county.) (Unofficial notes were recorded in C.S. File 58/82) V.Laugen, March 1997