

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 660500

PRIMARY CORNER DESCRIPTION E 1/16 Secs. 12 & 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15759)

-----

Point for the center E 1/16 sec. cor. of secs. 12 & 13.  
Set an iron post 28" long, 2½" dia., 20" in the ground, with brass cap marked:

E 1/16  $\frac{S\ 12}{S\ 13}$   
1975

from which  
A fir, 26" dia., bears N.83°W., 15 lks., mkd: E 1/16 S12 BT.  
A fir, 22" dia., bears S.19°W., 22 lks., mkd: E 1/16 S13 BT.

Douglas Co. Surveyors Office - Rod Kimberling - Stephen J Flause - Karen Cheney - May 16, 1977 - C.S. File 59/34-17

-----

Condition Report only  
Found - A 2½" iron pipe protruding 7" above ground, with a BLM brass cap (properly) marked.  
A D.Fir 22" dia., bears S.19°W., 14.3', open single blaze marked E 1/16 S13 BT.  
A D.Fir 25" dia., bears N.83°W., 9.9' (rec. 15 lks) open single blaze marked E 1/16 S12 BT.