

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 674129

PRIMARY CORNER DESCRIPTION W.P. old SW Cor. Sec. 31, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6519)

Set a post corner of secs. 1, 6, 31 and 36, corner of T29S R7W, from which

- A Laurel 4" dia., bears N.65°E., 9 lks. dist.
- A Laurel 6" dia., bears N.50°W., 25 lks. dist.
- A Laurel 10" dia., bears S.35°W., 17 lks. dist.
- A Laurel 20" dia., bears S.50°E., 24 lks. dist.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 6036-37)

At the Ford cor. of Tps. 29 and 30 S., Rs. 7 and 8 W., located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post 3 ft. long, 1" dia., 28" in the ground, for witness point, with brass cap mkd: WP 1924

from which the original bearing trees:

- A Laurel stump bears S.50°E., 24 lks. dist.
- A Laurel stump bears S.35°W., 17 lks. dist.
- A Laurel 30" dia., bears N.50°W., 25 lks. dist., marks are legible.

The NE. bearing tree is entirely destroyed.

New Bearing trees:

- A Chinquapin 20" dia., bears N.22°E., 72 lks. dist. mkd. WP BT.
- A Fir 30" dia., bears S.20°E., 49 lks. dist., mkd. WP BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell; Dale McFarland, crew - May/June 1962 - C.S. File 49/139-66

Found brass cap at corner and both BTs, now stumps.

New BTs- 7" Cedar bears S.75½°W., 37.1 ft. scribed W.P. CS S36.

18" Laurel bears N.4°W., 71.0 ft. scribed WP S36 CS BT.