

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 676177

PRIMARY CORNER DESCRIPTION W.P. - old W. ¼ sec. 31, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6519)

-----  
Set ¼ sec. post, from which  
A Laurel 10" dia., bears S.70°W., 25 lks. dist.  
A Laurel 8" dia., bears N.80°E., 10 lks. dist.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 5940-41)

-----  
Intersect the point for Ford's ¼ sec. cor. of secs. 31 and 36, located by measurement from the original bearing trees. At the exact cor. point  
Set an iron post 3 ft. long, 1" dia., 28" in the ground for witness point, with brass cap mkd. WP  
1924

From which the original bearing trees;  
A Laurel 18" dia., bears N.74°W., 25 lks. dist. (not S.70°W.) marks are legible.  
A Laurel 14" dia., bears S.80°E., 10 lks. dist. (not N.80°E.) marks are legible.  
New bearing trees:  
A Laurel 5" dia., bears N.51°E., 35 lks. dist. mkd. WP BT.  
A Fir 18" dia., bears S.73°E., 32 lks. dist. mkd. WP BT.