

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 677371

PRIMARY CORNER DESCRIPTION W.P. for old 1/4 Cor. Secs. 19 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6518)

Set ¼ sec. post, from which
A Laurel 12" dia., bears N.40°W., 11 lks. dist.
A Laurel 12" dia., bears S.43°E., 54 lks. dist.

(Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 - (DCSO records Vol. 14 Page(s) 5939-40)

Intersect the point for Ford's ¼ sec.cor. of secs. 19 and 24, located by measurement from the original bearing trees.
At the exact cor. point
Set an Iron post 3 ft. long, 1" dia., 28" in the ground for witness point, with brass cap mkd: WP
1924

from which the original bearing trees:
A Laurel 30" dia., bears N.33°W., 11 lks. dist. (not N.40°W.) marks grown over and not opened.
A Laurel 24" dia., bears S.42°E., 54 lks. dist. (not S.43°E.) marks grown over and not opened.
New bearing trees:
A Laurel 20" dia., bears N.8°E., 60 lks. dist. mkd. WP BT.
A Fir 6" dia., bears S.20°E., 19 lks. dist. mkd. WP BT.