

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 678566

PRIMARY CORNER DESCRIPTION W.P. from W. ¼ cor. Sec. 7, 29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6517)

-----  
Set ¼ sec. post, from which  
A B.Oak 12" dia., bears N.16°E., 38 lks. dist.  
A B.Oak 18" dia., bears S.40°W., 37 lks. dist.

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 5939)

-----  
Intersect the point for Ford's ¼ sec. cor. of secs. 7 and 12, located by record bearing and distance from the original NE. bearing tree.

At the exact cor. point  
Set an iron post 3 ft. long, 1" dia., 28" in the ground, for witness point, with brass cap mkd: WP  
1924

from which the original bearing tree:  
A B.Oak 24" dia., bears N.16°E., 38 lks. dist., marks grown over, not opened, blazes show plainly.

New bearing trees:  
A Fir 20" dia., bears N.65°E., 34 lks. dist., mkd. WP BT.  
A Fir 10" dia., bears S.44½°E., 19 lks. dist. mkd. WP BT.

BLM Resurvey by Daniel E. Weller and Dale T. Bedell, Cadastral Surveyor, under Group #1447, Surveyed June 1988/Feb. 1989 - (DCSO records Vol. 48 Page(s) 18532)

-----  
From the ¼ cor. sec.7,T29-7 only, the witness point established by Mensch in 1924, at the Ford position for the ¼ sec. cor. of secs. 7 and 12, bears N.82°46'00"W., 1.940 chs. dist., monumented with an iron post 1" dia., firmly set, projecting 1" above ground, with brass cap mkd. WP 1924 from which the remains of an original bearing tree:

An Oak stump 24" dia., bears N.16°E., 39 lks. dist., no marks remaining. (Rec. 38 lks.)

and the remains of a bearing tree by Mensch:  
A Fir stump 18" dia., bears N.65°E., 34 lks. dist., with scribe marks BT visible on rotted blaze.

and the remains of bearing trees mkd. by Byron in 1960:  
A Fir 18" dia., bears S.28°W., 60 lks. dist. with healed blaze.

A Fir stump 8" dia., bears S.42°W., 47 lks. dist., no marks visible.

and a new bearing tree:  
A Fir 9" dia., bears N.7°E., 22 lks. dist. mkd. X at breast height and BT at the base.

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 678566

PRIMARY CORNER DESCRIPTION W.P. from W. 1/4 cor. Sec. 7, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Nov. 2, 1960 - C.S. 49/139-3  
-----  
Found Brass cap at corner and BTs as recorded by Mensch in 1924. All are now stumps. I open NE. BT and find good scribing "B".  
New BTs- 7" R.Fir bears S.42°W., 31.0 ft. scribed W.P. CSBT  
          10" R.Fir bears S.28°E., 40.4 ft. scribed W.P. CSBT

---

FD. 2 BTs & straightened BC by Ken Hoffine, 8/2007 - M154-14