

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6517)

-----  
Set post cor. of secs. 1, 6, 7 and 12, from which  
A B.Oak 15" dia., bears N.46°W., 142 lks. dist.  
A B.Oak 12" dia., bears N.45°W., 52 lks. dist.  
A W.Oak 12" dia., bears N.63°E., 225 lks. dist.  
A B.Oak 20" dia., bears S.21°E., 110 lks. dist.

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 5938)

-----  
Intersect the point for Ford's cor. of secs. 1, 6, 7, and 12, restored by Hathorn's record tie.  
Set an iron post 3 ft. long, 1" dia., 28" in the ground, for witness point, with brass cap mkd. WP  
1924

from which  
A W.Oak 32" dia., bears N.55°E., 136 lks. dist. mkd. WP BT  
A W.Oak 12" dia., bears S.21°E., 167 lks. dist. mkd. WP BT

H.L. Eppstein - Wit: N.E. Richardson; H.E. Ireland - March 6, 1931 - C.S. File 18/2

-----  
Witness corner to section 6 and 7, 119.0 ft. West of corner of standard govt. corner, marked W.P., from which  
A 36" W.Oak N.57°E., 89.0 ft.

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy - Teresa Buley, Wit. - Nov. 3, 1981 - C.S. File 61/29-21

-----  
Found - Did not find the 1924 brass cap as it appears to be buried by a new driveway fill, approx. 7 ft. deep.  
32" now 42" W.Oak with good scar (Rec. N.55°E., 89.8 ft. per resurvey) (Rec. N.57°E., 89.0 ft. per 1931)  
12" now 18" W.Oak stump in poor condition with scribed "WP BT" visible (Rec. S.21°E., 110.2 ft. per resurvey)  
Brass cap for section corner common to secs. 6 and 7 only of T29-7 (Rec. West 119.0 ft. per 1931) mkd. T29S S6 S7 R7W 1924  
Using both original BTs, I SET a brass cap at record brg. & dist. mkd: Douglas Co. Surveyor WP 1981.  
(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 678616

PRIMARY CORNER DESCRIPTION W.P. for cor. Secs 6 & 7 only, T29-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

1981 B.C. bears S.55°W., 89.8 ft. from 32" now 42"  
W.Oak.  
1981 B.C. bears N.21°W., 110.2 ft. from 12" now 18"  
W.Oak.  
1981 B.C. is on westerly edge of driveway and  
protrudes 3" above ground.  
New BTs- 20" Fir scribed "WPCS BT" in double blaze, bears  
S.64°W., 19.1 ft.  
20" Cedar scribed "WPCS BT" in double blaze bears  
N.56°W., 6.3 ft. Note: This tree to be removed  
by landowner. C.S. File 62/7  
12" Fir scribed "WPCS BT" in double blaze bears  
S.33°E., 85.4 ft.  
The found B.C. for sec. cor. to 6 & 7, T29-7 only,  
bears S.89°E., 119.2 ft.  
Sketch in C.S. File 61/29