

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 700273

PRIMARY CORNER DESCRIPTION West ¼ Sec. to 30 only, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6017)

Intersect the center latitudinal subd. line of original Sec. 30 T29S-7, S.80°06'E., 2.90 chs. from the Ford ¼ sec. cor. of secs. 25 & 30, restored as cor. #3 of Tract #54.

At the point of intersection
Set an iron post 3 ft. long, 1" diam., 28" in the ground, for resurvey ¼ Sec. 30 only T29S R7W, with brass cap mkd.

¼S30
1924

from which

- A Fir, 26" diam., bears N.17°E., 76 lks., marked ¼ S 30 BT
- A Fir, 30" diam., bears S.20°E., 41 lks., marked ¼ S 30 BT

James W. Byron, Dep. Co. Surveyor - John Powell and Wm. Stoffel - July 1962 - C.S. 49/139-95

Found - Brass cap at corner & both BT's., now stumps, show good scars.

New BTs -16" Laurel, bears N.23°E., 75.3 ft., scribed W ¼ S30 CS BT.

9" Laurel, bears N.56°W., 26.5 ft., scribed W ¼ S30 CS BT.

Found O.K. - GLO Resurvey - Wayne Rogers - Group #1454 - Aug 1988/May 1989 (DCSO records Vol. 49 Page 18737)

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2072, surveyed Aug. 2006 (DCSO rec. Vol. 55 pg(s) 21426-7)

The ¼ sec. cor. of sec. 30 only, T.29S., R.7W., monumented with an iron post, 1" dia., firmly set, projecting 16" above the ground, with brass cap (properly) mkd

from which the remains of bearing trees mkd. by Mensch

A sawed fir stump, 34" dia., bears N.17°E., 50.2 ft., with a healed blaze.

A sawed fir stump, 35" dia., bears S.20°E., 27.1 ft., with fragmentary scribe marks visible on an opened blaze.

and BTs marked by Byron, Deputy County Surveyor, in 1962

A madrone, 16" dia., bears N.21°E., 75.2 ft., with a healed blaze.

A madrone, 24" dia., bears N.52½°W., 26.4 ft., with a healed blaze.