

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor for 24 & 25 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated
April 12, 1855 (DCSO records, Vol. 16 Page 6571)

Set post for sec. cor. 19, 30, 24, 25 from which
A Fir, 30" diam., bears S.20°W., 6 lks.
A Fir, 12" diam., bears S.42°E., 46 lks.
A Fir, 12" diam., bears N.42°W., 40 lks.
A Laurel, 15" diam., bears N.25°E., 58 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy
Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Pg.
6016)

Intersect the point for Hathorn cor. sec. of 19, 24, 25, &
30, located by measurement from the original bearing trees.
At the exact cor. point

Set an iron post, 3 ft. long, 2" diam., 28" in the ground,
for cor. of secs. 24 & 25 only, with brass cap mkd.

T29S:
S24 1924
S25
R8W

from which (the original bearing trees)

A laurel, bears N.25°E., 56 lks., rotted down, stump shows
position.

A laurel, 16" diam., bears S.42°E., 46 lks., marks grown
over, blazes plain.

A fir, 40" diam., bears S.20°W., 6 lks., marks are plain
on the bark.

A laurel, 12" diam., bears N.42°W., 40 lks., marks grown
over, blazes are plain.

New bearing trees:

A cedar, 24" diam., bears S.15°W., 60 lks., marked T29S
R8W S25 BT.

A fir, 8" diam., bears N.65°W., 48 lks., marked T29S R8W
S24 BT.

James W. Byron, Dep. Co. Surveyor - John Powell and Wm.
Stoffel - July 1962 - C.S. 49/139-95

Found - Brass cap at corner. Both BT's, now down.

New BTs -8" Cedar, bears N.50°W., 17.7 ft., scribed S24 CS BT
5" R.Fir, bears S.72°W., 15.2 ft., scribed S25 CS BT

Found O.K. - BLM Resurvey - Wayne Rogers - Group #1454 - Aug
1988/May 1989 (DCSO records Vol. 49 Page 18738)