

PRIMARY CORNER DESCRIPTION E. ¼ cor. to sec 24 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 16 PG. 6571)</p> <p>-----</p> <p>Set ¼ sec. post, from which A laurel, 12" diam., bears S.81°E., 20 lks. A laurel, 6" diam., bears N.12°W., 30 lks.</p>
<p>Re-establishment of corners - Fred Mensch , U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6015)</p> <p>-----</p> <p>Intersect the point for Hathorn's ¼ sec. cor. 19 & 24, located by measurement from the original bearing trees on which the marks are legible. At the exact cor. point Set an iron post 3 ft. long, 1" diam., 28" in the ground, for ¼ sec. cor. of sec. 24 only, with brass cap mkd. ¼S24 1924 from which (the original bearing trees) A laurel, 20" diam., bears S.81°E., 20 lks. A laurel, 18" diam., bears N.12°W., 30 lks. New bearing trees: A fir, 20" diam., bears S.5°W., 37 lks., marked ¼ S 24 BT A fir, 10" diam., bears N.69°W., 32 lks., marked ¼ S 24 BT</p>
<p>FD. OK. - Jan. 10, 1980 - H. Johnstone - M 81 - 75</p>
<p>FD. OK. - BLM Resurvey - Daniel E. Weller & Dale T. Bedell - Group # 1447 - June 1988/Feb 1989 (DCSO records Vol. 48 Page 18529)</p>
<p>Mark Smalley, L.S. #2354 - For: Kenneth & Hallie Ford - Dec. 1994 -M 121-51</p> <p>-----</p> <p>Found - 1924 GLO brass cap & iron rod. 24" Madrone, N.12°W., 19.8', snag. 19" Fir, N.69°W., 21.1', healed. 24" Madrone, S.81°E., 13.2', stump. 34" Fir, S.5°W., 24.4', healed. New BTs- 14" Fir, North 13.6', "¼ S BT" 10" Cedar, N.84°E., 21.3', "¼ S BT"</p>
<p>1</p>