

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 700427

PRIMARY CORNER DESCRIPTION Sec. Cor to 18 & 19 only, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original (corrective re survey) - Fred Mensch, U.S. Deputy Surveyor - under date of Dec. 4, 1924 (DCSO Vol. 14 Page 6013)

Intersect the line bet. secs. 18 and 19, S.75°02'E., 2.97 chs. from the Ford cor. of secs. 13, 18, 19, 24, restored as cor. No. 3 of tract #52.

At the point of intersection
Set an iron post, 3 ft. long, 2" diam., 28" in the ground, for resurvey cor. of secs. 18 and 19 , with brass cap mkd.
:T29S
:S18
:S19
:R7W
1924

from which
A Fir, 44" diam., bears N.34°E., 42 lks., mkd. T29S R7W
S18 BT.
A Yew, 10" diam., bears S.70°E., 12 lks., mkd. T29S R7W
S19 BT.

James W. Byron, Dep. Co. Surveyor - John Powell and Dale McFarland - May/June 1962 - C.S. 49/139-74

Found - Brass cap at corner & now 16" Yewood, shows good scribing on rotted face bears S.3½°E., 7.9 ft. not S.70°E.

NE. bearing trees now stump
New BT:
Rescribe, now 16" Yewood, S3½°E., 7.9 ft., S19 T29S R7W
CS BT.
6" Fir, bears N.86°E., 26.7 ft., scribed S18 CS BT