

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 700467

PRIMARY CORNER DESCRIPTION West ¼ corner to sec. 18 only, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6011-12)

Intersect the center latitudinal subd. line of sec. 18, S.81°54'E., 2.78 chs. from the Ford ¼ sec. cor. of secs. 13 & 18, restored as cor. # 3 of Tract # 50, identical with cor. # 2 of Tract # 51.

At the point of intersection
Set an iron post 3 ft. long, 1" diam., 28" in the ground, for resurvey ¼ sec. cor. of sec. 18 only, with brass cap marked.

¼S18
1924

from which

A B. Oak, 30" diam., bears N.52°E., 29 lks., marked ¼ S 18 BT.

A Pine, 60" diam., bears S.31°E., 64 lks., marked ¼ S 18 BT.

James W. Byron, Dep. Co. Surveyor - John Powell and Dale McFarland - May 1962 - C.S. 49/139-73

Found - Brass cap at corner & NE. BT. SE. BT., now stump hole only.

New BT - 7" R.Fir, bears S.48°E., 12.6 ft. scribed ¼ S18 CS BT.

Fd. Ok. - L. Monrean - Co. Surveyors Office - 2/3/77 - C.S. 59/29-22