

PRIMARY CORNER DESCRIPTION WC E ¼ cor. to sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated
April 12, 1855 (DCSO records, Vol. 16 Page 6569)

Set ¼ sec. post from which
An Ash, 15" diam., bears N.12½°E., 588 lks.
An Ash, 6" diam., bears S.30°W., 127 lks.
Waters house bears S.79°W.

Re-establishment of corners - Fred Mensch , U.S. Deputy
Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page
6007)

As the true point for ¼ sec. cor. of sec. 1 only falls in
cultivated grain field where it is impracticable to establish
a permanent cor.

Set an iron post, 3 ft. long, 1" diam., 28" in the ground,
for witness cor. to the ¼ sec. cor. of sec. 1 only, with
brass cap marked

¼S1:
WC
1924

from which

A W. Oak, 36" diam., bears N.38¼°W., 411 lks., marked WC
¼ S1 BT.

No other bearing tree or other object available, no stones
available for mound.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 4/10/2001 - C.S. File 66/21-9

Found - (WC) 1" I.D. iron pipe protrudes 1" above ground
brass cap gone. (1924)

36" now 36" dia. down, a burnt Oak no scribing found
burnt stump base, bears N.38¼°W., 271.3 ft.

New - 5/8" iron rod @ fence corner bears S.74½°E. 85.17 ft
6"x6" by 4 ft. pressure treated wood post "AT&T
FIBER OPTIC WARNING #586" bears N.61°E., 82.2 ft.
20" dia., Ash single blazed & scribed "WC E ¼ S1 CS
BT" bears N.49½°W., 286.0 ft.

5/8" iron rod near fence corner bears N.72 3/4°E.,
307.3 ft.

5/8" iron rod with alum. cap stamped "ODOT HORIZ
CONTROL 35" bears S.61¼°W., 556.9 ft.

Note - Compass decl. 17 3/4°E.

Corner lies 30 ft. south of centerline State Hwy 42.

Witness post & sign set 1 ft. south of corner.

See last Pg for pictures.

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION WC E 1/4 cor. to sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

