

PRIMARY CORNER DESCRIPTION NW Cor. Tract #49 (AP #2)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6517)

-
- Set a post cor. of secs. 7, 12, 13, and 18, from which
- A B.Oak 18" dia., bears N.45°W., 5 lks. dist.
 - A B.Oak 10" dia., bears S.73°W., 62 lks. dist.
 - A B.Oak 8" dia., bears N.20°E., 76 lks. dist.
 - A B.Oak 8" dia., bears S.75°E., 140 lks. dist.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 5990-91)

Intersect to point for Ford's cor. of secs. 7, 12, 13, and 18, located by measurement from the original bearing trees, on which the blazes show plainly, but marks are grown over, as follows:

- A B.Oak 22" dia., bears N.21°E., 77 lks. dist. (not N.20°E. 76 lks.)
- A B.Oak 28" dia., bears S.77½°E., 140 lks. dist. (not S.75°E.)
- A B.Oak 24" dia., bears S.70°W., 62 lks. dist. (not S.73°W.)
- A B.Oak 30" dia., bears N.45°W., 5 lks. dist.

At the exact cor. point

Set an iron post 3 ft. long, 1" dia., 28" in the ground for cor. No. 2 of this survey, with brass cap mkd. _____

:AP 2
:TR 49
1924

from which

- A Fir 20" dia., bears S.70°E., 18 lks. dist. mkd. AP 2 TR 49 BT.