

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 922110

PRIMARY CORNER DESCRIPTION SW Cor. TR #50 (AP #3)

Alias <u>923110</u>	Description <u>NW Cor. TR #51 (AP #2)</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6518)

Set $\frac{1}{4}$ sec. post, from which
A B.Oak 6" dia., bears S.73°E., 112 lks. dist.
A B.Oak 8" dia., bears N.3°W., 1005 lks. dist.

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 5993)

Intersect the point for the Ford $\frac{1}{4}$ sec. cor. of secs. 13 and 18, located by measurement from the original bearing trees, as follows:

A B.Oak 30" dia., bears N.73°E., 112 lks. dist.
A B.Oak 24" dia., bears N.0°30'W., 105 lks. dist. (Not N.3°W., 1005 lks.), marks are grown over and not opened.

At the exact cor. point
Set an iron post 3 ft. long, 1" dia., 28" in the ground for cor. No. 3 of Tract No. 51, with brass cap marked:

:Tr 50
:AP 3

:AP 2
:TR 51
1924

from which
A B.Oak 16" dia., bears N.28°W., 42 lks. dist. mkd. A P 3 TR 50 BT.
A Pine 6" dia., bears S.13°E., 86 lks. dist. mkd. A P 2 TR 51 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Dale McFarland, crew - May/June 1962 - C.S. File 49/139

Found - 1924 Brass cap at corner.
NE. BT, now snag, shows good scar.
SE. BT gone.
New BTs- 8" R.Fir N.12°E., 28.7 ft. scribed AP 3 Tr 50 CS BT.
R.Fir S.16°E., 10.9 ft. scribed AP 2 Tr 51 CS BT.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Karen Cheney; P.L. Earle, crew - Feb. 3, 1977 - C.S. File 59/29-23

CORNER REPORT ONLY
(Cont. Next Page)

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 922110

PRIMARY CORNER DESCRIPTION SW Cor TR #50 (AP #3)

Alias 923100 Description NW Cor TR #51 (AP #2)

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Found - A 1" I.P. 14" high with 1924 GLO brass cap properly stamped.

Corner is at the NW. corner of a large natural clearing. (Rock bluff)

A B.Oak 6" now 38", bears S.71°E., 73.9 ft. (Rec. S.73°E.) Due to size of tree, blaze not visible, I do not open for scribing.

A B.Oak 8" now 30", bears N.0½°E., 70.5 ft. (Rec. N.0½°W., 69.3 ft.). Due to size of tree, blaze not visible, I do not open for scribing.

A B.Oak 15" now down and rotting bears N.28°E., 27.7 ft. Tree has old blaze.

SE BT per 1924 survey is not found.

A R.Fir 8" now 15", bears N.12°E., 28.7 ft. Tree has well healed double blaze.

A R.Fir 14" bears S.16°E., 11.3 ft. (Rec. 10.9 ft.) Tree has well healed double blaze.