

PRIMARY CORNER DESCRIPTION SW. Cor. TR #52 (AP #3)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6518)

Set a post cor. of secs. 3, 18, 19, and 24, from which
A Yew 20" dia., bears N.15°E., 95 lks. dist.
A Red Fir 6" dia., bears S.75°W., 27 lks. dist.
A Red Fir 12" dia., bears S.45°E., 46 lks. dist.
A Red Fir 6" dia., bears N.20°W., 45 lks. dist.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 5996)

Intersect the point for Ford's cor. of secs. 13, 18, 19, and 24, located by measurement from the two original bearing trees as follows:

A Fir 18" dia., bears S.75°W., 27 lks. dist.
A Fir 24" dia., bears N.22°W., 45 lks. dist. (Not N.20°W.)
marks grown over and not opened.
SE. and NE. trees gone, but stump holes serve futher to identify the cor. point.

At the exact cor. point

Set an iron post 3 ft. long, .1" dia., 28" in the ground for cor. No. 3 of this survey, with brass cap mkd. :TR 52
:AP 3
1924

from which

A Fir 14" dia., bears N.17½°E., 38 lks. dist. mkd. AP 3 TR 52 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz; Larry E. Monrean; P. L. Earle; K. Cheney; A. Vic Cangie; Mike Tompkins - Jan. 31, 1977 - C.S. File 59/29-18

Found 1924 brass cap on 1" I.P. extending 12" above ground properly marked, from which

The only remaining orig. BT, a 6" now 36" D.Fir, alive with no apparent scar, bears N.22°W., 29.7 ft.
A 1924 BT, a 14" now 24" D.Fir alive and well healed bears N.19°E., 25.1 ft. (Rec. N.17½°E., 25.1 ft.)