

PRIMARY CORNER DESCRIPTION NW. Cor. TR #53 (AP #2)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6518)

-
- Set post cor. of secs. 19, 24, 25 and 30, from which
- A Laurel 18" dia., bears N.12°E., 100 lks. dist.
 - A Laurel 15" dia., bears S.70°W., 75 lks. dist.
 - A B.Oak 15" dia., bears S.25°E., 37 lks. dist.
 - A B.Oak 12" dia., bears N.83°W., 67 lks. dist.

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 5997-98)

Intersect the point for the Ford Co. of secs. 19, 24, 25 and 30, located by measurement from the original bearing trees, as follows:

- A B.Oak 24" dia., bears S.21°E., 37 lks. dist. (Not S.25°E.)
- A B.Oak 24" dia., bears N.83°W., 67 lks. dist., marks on both these trees grown over and not opened.
- A Laurel 20" dia., bears S.67°W., 75 lks. dist. (Not S.70°W.) marks rotted away.
- A Laurel stump bears N.12°E., 90 lks. dist. (Not 100 lks.)

At the exact cor. point
Set an iron post 3 ft. long, 1" dia., 28" in the ground, for cor. No. 2 of this survey, with brass cap marked:

:AP 2
:TR 53
1924

from which

- A B.Oak 52" dia., bears S.66°E., 71 lks. dist. mkd. AP 2 TR 53 BT.