

PRIMARY CORNER DESCRIPTION SW Cor. TR 54 (AP #3)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6519)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.65°E., 28 lks. dist.
A Laurel 7" dia., bears N.40°W., 54 lks. dist.

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 5999-6000)

The point for Ford's ¼ sec. cor. of secs.25 and 30, located by Hathorn's record tie from the Hathorn cor. of secs. 19, 24, 25 and 30. No trace of Ford's old cor. could be found. Set an iron post 3 ft. long, 1" dia., 28" in the ground for cor. No. 3 of this survey, with brass cap mkd: :TR 54
:AP 3
1924

from which
A Laurel 16" dia., bears N.57°E., 98 lks. dist. mkd. AP 3
TR 54 BT.

Fd. and Used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1454, surveyed Aug. 1988/May 1989 - (DCSO records Vol. 49 Page(s) 18740)

David Edwards - Brant Miller & Eric Sprinkle - 6/22/2012 - C.S. File 65/77-7

Found - 1924 GLO iron post and brass cap (properly mkd).
A 24" dia. Madrone with healed blaze bears N.57°E.,
64.7 feet. (1924 BT)

New - A 9" dia. Cedar scribed "T29S R8W S25 BT" bears
S.81°W., 9.25 ft.
Compass decl. 18°E.