

PRIMARY CORNER DESCRIPTION NW Cor. TR #55 (AP #2)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 6001)

Point for the S. 1/16 sec. cor. on W. bdy. of original sec. 30, T29-7 - (NOT 1/16 now.)
Set an iron post 3 ft. long, 1" dia., 28" in the ground for cor. No. 2 of this survey, with brass cap marked:

:AP 2
:TR 55
1924

from which
A Fir 28" dia., bears S.16°E., 53 lks. dist. mkd. AP 2 TR 55 BT.

Cor. Fd. and Used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1454, surveyed Aug. 1988/May 1989 - (DCSO records Vol. 49 Page(s) 18740)

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2072, surveyed Aug. 2006 (DCSO rec. Vol. 55 pg(s) 21428)

Corner No. 2, Tract 55, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by Mensch
A sawed fir stump, 40" dia., bears S.16°E., 35.0 ft., with a healed blaze.

and new bearing trees
A cedar, 7" dia., bears S.7¼°E., 47.5 ft., mkd. AP2 TR55 S25 BT.

A fir, 9" dia., bears N.83½°W., 17.8 ft., mkd. AP2 S25 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description