

TOWNSHIP 29 RANGE 08 POINT IDENTIFIER # 927110

PRIMARY CORNER DESCRIPTION SW. Cor. TR #55 (AP #3)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6519)

-----  
Set post corner of secs. 25, 30, 31 and 36, from which  
A Laurel 4" dia., bears S.10°E., 44 lks. dist.  
A Laurel 4" dia., bears S.30°W., 25 lks. dist.  
A Laurel 5" dia., bears N.50°W., 19 lks. dist.  
A Laurel 6" dia., bears N.65°E., 37 lks. dist.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 6002)

-----  
Intersect the point for Ford's cor. of secs. 25, 30, 31 and 36, located by measurement from the stump holes of the original bearing trees. The bearing trees have completely rotted away.

At the cor. point

Set an iron post 3 ft. long, 1" dia., 28" in the ground for cor. No. 3 of this survey, with brass cap mkd. :TR 55

:AP 3  
1924

from which

A Fir 20" dia., bears N.46°E., 21 lks. dist. mkd. AP 3 TR 55 BT.

Cor. Fd. and Used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1454, surveyed Aug. 1988/May 1989 - (DCSO records Vol. 49 Page(s) 18741)