

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 037010

PRIMARY CORNER DESCRIPTION NW Cor. Wm. P. Day DLC #37

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - (DCSO records, DLC Volume, Page 589)

-----  
Set a post from which  
An Ash 10" dia., bears S.60°E., 243 lks.

J. W. Cole, Deputy - McHenry and Wolford, witnesses - Sept. 1920 - Vol. 3 Page 70; Field book 48 Pg. 10; C.S. File 6/17

-----  
Find original BT alive and standing. Went to the tree and run N.60°W., 243 lks. with var 21°15'E. Set a pin and find that the original ground had been excavated to turnpike the road and the distance and directions given put the point 6½ lks. North of the DLC line as designated by the fences between R. Dick and Stanley property. Also, Jake Denn testifies that the corner formerly stood on fence line. I used this as evidence and moved point South 6½ lks. and established the corner as recorded in Book of Corner Records.

G.G. Stewart - Wit: W.S. Crear; E.J. Kennedy - May 22, 1922 - Vol. 3 Page 121

-----  
Set from original BT. Set a 1¼" x 36" Iron pipe for corner.

Fd. 1¼" Pipe in road and Ash BT, S.60°E., 243 lks. by A. Boyer May 1938 - C.S. File 32/13

Survey by H. Northcraft - For: Eugene Banks - Oct. 1976 - M 61-80

-----  
Found - 1¼" Iron pipe.  
Ash, S.60°E., 160.38 ft., identified by O. Standly.  
New BT - 15" W.Oak N.32°E., 233.4 ft. scribed "NW Cor Cl. 37 T29S R9W".