

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 037020

PRIMARY CORNER DESCRIPTION SW Cor. Wm. P. Day DLC #37

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - (DCSO records, DLC Volume, Page 588)

Set a post from which
A Fir 20" dia., bears N.45°E., 31 lks.

Douglas Co. Surveyors office - James W. Byron, Deputy - John Powell, crew - July 3, 1962 - C.S. File 49/139-91

Found - Orig. 20" R.Fir N.45°E., 20.5 ft., shows good scribing "BT" on old face, now stumps.
Set brass cap at cor. and mkd: County Surveyors office 1962
S.W. D.L.C. 37 T29S R9W
New BT - 10" W.Fir bears N.22°W., 11.7 ft. scribed CL 37 CS BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #584 - Surveyed July 1965 - (DCSO records Vol. 33 Page(s) 13882)

The SW. cor. DLC #37, perpetuated and recorded by Byron in 1962, monumented with an iron post 1½" dia., firmly set, extending 20" above ground with brass cap mkd. in 1962, from which the remains of the original bearing tree
A sawed Fir stump 43" dia., bears N.43°E., 33 lks. dist, mkd. BT on opened blaze. (Rec. N.45°E., 31 lks.)
and a bearing tree mkd. by Byron:
A Fir 11" dia, bears N.23½°E., 18½ lks. dist. mkd. LC 37 CS BT.
and new bearing trees
A Fir, 8" dia., bears N.29¼°E., 79 lks. dist. mkd. DLC 37 BT.
A Fir 6" dia., bears N.56°E., 77 lks. dist. mkd. DLC 37 BT.
A Fir 7" dia., bears S.55°W., 7 lks. dist. mkd. S36 BT.
Add the marks BLM 1965 to top of brass cap.

Fd. OK, 1975 by OSHD - "N-8"